

**CABLE VIKON® CONTROL-LS TIPO PVC+PVC 600 V, 75/90°C SECCION (CALIBRE) 0,823 5 mm² (18 AWG) ESPESOR DE AISLAMIENTO: 0,76 mm**

Item Number	Number of Conductors	Jacket Thickness	Approx. Overall Diameter	Approx. Total Weight
		mm	mm	kg/100 m
N488	2	1,14	8,1	7
Y911	3	1,14	8,5	9
L220	4	1,14	9,3	11
Q349	5	1,14	10,1	13
T518	6	1,14	10,9	15
I399	7	1,14	10,9	16
W083	8	1,14	11,8	18
CS64	9	1,14	12,7	20
I103	10	1,14	13,6	23
D885	12	1,52	14,8	29
CS65	14	1,52	15,6	32
CS66	15	1,52	16,4	34
V554	16	1,52	16,4	36
C656	19	1,52	17,2	40
CS67	21	1,52	18,1	44
CS68	23	1,52	19,0	48
F141	24	1,52	19,9	51
CS69	27	1,52	20,3	55
X316	30	1,52	21,1	61
CS70	33	2,03	22,9	71
CS71	37	2,03	23,8	77

**NOTE: Dimensions and weights are subjected to manufacturing tolerances.**