

CABLE VIAKON® FOTOVOLTAICO PV, EPR+CPE, 600 V, 90°C

Calibre	Área nominal de la sección transversal	Número de hilos	Espesor nominal del aislamiento	Espesor nominal de la cubierta	Diámetro total aproximado	Peso total aproximado
AWG / kcmil	mm ²		mm	mm	mm	kg / 100m
14	2.082	7	0.76	0.76	5.2	5
12	3.307	7	0.76	0.76	5.6	6
10	5.26	7	0.76	0.76	6.2	9
8	8.367	7	1.14	0.76	7.7	13
6	13.3	7	1.14	1.14	9.4	20
4	21.15	7	1.14	1.14	10.6	29
2	33.62	7	1.14	1.14	12.1	42
1	42.41	19	1.4	1.52	14.6	55
1/0	53.48	19	1.4	1.52	15.6	67
2/0	67.43	19	1.4	1.52	16.7	81
3/0	85.01	19	1.4	1.52	18	99
4/0	107.2	19	1.4	1.52	19.4	122
250	126.7	37	1.65	2.03	22.2	148
300	152	37	1.65	2.03	23.6	173
350	177.3	37	1.65	2.03	24.8	198
400	202.7	37	1.65	2.03	26	224
500	253.4	37	1.65	2.03	28.1	274
600	304	61	2.03	2.03	30.9	327
750	380	61	2.03	2.03	33.5	401
1000	506.7	61	2.03	2.03	37.2	523

Nota: Las dimensiones y pesos están sujetos a tolerancias de manufactura.

