

CABLE VIAKON® FOTOVOLTAICO PV, EPR+CPE, 2000 V, 90°C

Calibre	Área nominal de la sección transversal	Número de hilos	Espesor nominal del aislamiento	Espesor nominal de la cubierta	Diámetro total aproximado	Peso total aproximado
AWG / kcmil	mm ²		mm	mm	mm	kg / 100m
14	2.082	7	1.14	0.76	5.9	6
12	3.307	7	1.14	0.76	6.4	7
10	5.26	7	1.14	0.76	7	10
8	8.367	7	1.4	0.76	8.3	14
6	13.3	7	1.4	1.14	10	21
4	21.15	7	1.4	1.14	11.2	30
2	33.62	7	1.4	1.14	12.6	43
1	42.41	19	1.65	1.52	15.1	57
1/0	53.48	19	1.65	1.52	16.1	69
2/0	67.43	19	1.65	1.52	17.2	83
3/0	85.01	19	1.65	1.52	18.5	101
4/0	107.2	19	1.65	1.52	19.9	124
250	126.7	37	1.91	2.03	22.8	150
300	152	37	1.91	2.03	24.1	176
350	177.3	37	1.91	2.03	25.4	201
400	202.7	37	1.91	2.03	26.5	227
500	253.4	37	1.91	2.03	28.7	277
600	304	61	2.29	2.03	31.4	331
750	380	61	2.29	2.03	34	405
1000	506.7	61	2.29	2.03	37.8	528

Nota: Las dimensiones y pesos están sujetos a tolerancias de manufactura.

|